

## Combinaisons S-System

N° art.	Produit	Prix*		Configuration V1	Configuration V2	Configuration V3	Configuration V4	Configuration V5	Configuration V6	Configuration V7	Configuration V8	Configuration V9	Configuration V10	Configuration V11	Configuration V12	Configuration V13
<b>Profils</b>																
AK5600	Profil S511, SANS couvercle, alu, L: 2m	75.00	A	●	●	●	●	●	●	●	●	●	●	●	●	●
AK5600.B	Profil S511, SANS couvercle, noir, L: 2m	82.00	A	●	●	●	●	●	●	●	●	●	●	●	●	●
AK5600.W	Profil S511, SANS couvercle, blanc, L: 2m	82.00	A	●	●	●	●	●	●	●	●	●	●	●	●	●
AK5630	Profil S511, SANS couvercle, alu, L: 3m	111.00	A	●	●	●	●	●	●	●	●	●	●	●	●	●
AK5630.B	Profil S511, SANS couvercle, noir, L: 3m	121.00	A	●	●	●	●	●	●	●	●	●	●	●	●	●
AK5630.W	Profil S511, SANS couvercle, blanc, L: 3m	121.00	A	●	●	●	●	●	●	●	●	●	●	●	●	●
AK5700	Profil S512, SANS couvercle, alu, L: 2m	42.00	A		●	●	●	●	●	●	●	●	●	●	●	
AK5700.B	Profil S512, SANS couvercle, noir, L: 2m	51.00	A		●	●	●	●	●	●	●	●	●	●	●	
AK5700.W	Profil S512, SANS couvercle, blanc, L: 2m	51.00	A		●	●	●	●	●	●	●	●	●	●	●	
AK5730	Profil S512, SANS couvercle, alu, L: 3m	59.00	A		●	●	●	●	●	●	●	●	●	●	●	
AK5730.B	Profil S512, SANS couvercle, noir, L: 3m	72.00	A		●	●	●	●	●	●	●	●	●	●	●	
AK5730.W	Profil S512, SANS couvercle, blanc, L: 3m	72.00	A		●	●	●	●	●	●	●	●	●	●	●	
<b>Couvercles</b>																
AK5500	Couvercle pour F511, S511 & S512, opalin, L: 2m	34.00	A	●	●	●	●	●	●	●	●	●	●	●	●	
AK5530	Couvercle pour F511, S511 & S512, opalin, L: 3m	51.00	A	●	●	●	●	●	●	●	●	●	●	●	●	
<b>Embouts</b>																
AK5650	Embout A, pour profil S511 aluminium	5.70	A	●	●	●	●	●	●	●	●	●	●	●	●	●
AK5650.B	Embout A, pour profil S511 noir	5.70	A	●	●	●	●	●	●	●	●	●	●	●	●	●
AK5650.W	Embout A, pour profil S511 blanc	5.70	A	●	●	●	●	●	●	●	●	●	●	●	●	●
AK5750	Embout C, pour S511-S512, aluminium	5.70	A					●								
AK5750.B	Embout C, pour combinaison S511-S512 noir	5.70	A					●								
AK5750.W	Embout C, pour combinaison S511-S512 blanc	5.70	A					●								
AK5755	Embout D, pour S511-S512, alu	5.70	A								●					
AK5755.B	Embout D, pour S511-S512 noir	5.70	A								●					
AK5755.W	Embout D, pour S511-S512 blanc	5.70	A								●					
AK5760	Embout B, pour profil S511 aluminium	5.70	A						●	●		●		●		●
AK5760.B	Embout B, pour profil S511 noir	5.70	A						●	●		●		●		●
AK5760.W	Embout B, pour profil S511 blanc	5.70	A						●	●		●		●		●
<b>Accessoires</b>																
AC2400	Connecteur AC162 STS/ 2 LED	0.90	A		●	●	●	●	●	●	●	●	●	●	●	
AC9500	Kit suspension NL-1	33.00	A	●	●	●	●	●	●	●	●	●	●	●	●	
AK4660	Set de 2x inserts type M3, droits	18.00	A	●	●	●	●	●	●	●	●	●	●	●	●	
AK4665	Set de 2x inserts type M3, angle 90°	21.00	A	●	●	●	●	●	●	●	●	●	●	●	●	
AK5370	Plaque avec bornier interne, pour S511	27.00	A			●	●	●	●	●	●	●	●	●	●	
AK5377	Plaques de fixation pour alimentation, pour S511, /paire	14.00	A			●	●	●	●	●	●	●	●	●	●	
AK5378	2x Vis de fixation pour driver, pour S511	1.60	A					●	●			●	●			
AK5890	Clip de montage pour S511	12.00	A	●	●	●	●	●	●	●	●	●	●	●	●	

**Combinaisons S-System**

N° art.	Produit	Prix*		Configuration V1	Configuration V2	Configuration V3	Configuration V4	Configuration V5	Configuration V6	Configuration V7	Configuration V8	Configuration V9	Configuration V10	Configuration V11	Configuration V12	Configuration V13
<b>Convertisseurs variables</b>																
PSDDL24150	Convertisseur XOLED Linear Powerdim 24150, DALI & TouchDim, 24V 150W	180.00	A				•	•		•	•					
PSDDL24240	Convertisseur XOLED Linear Powerdim 24240, DALI & TouchDim, 24V 240W	222.00	A			•	•			•	•					
<b>Convertisseurs</b>																
PSDL2430	Convertisseur, 24V 30W	52.00	A	•	•	•	•			•	•					
PSDL2460	Convertisseur, 24V 60W	77.00	A	•	•	•	•			•	•					
PSDL2460W	Convertisseur IP66, 24V 60W	96.00	A		•	•				•	•					
PSDL24100	Convertisseur, 24V 100W	111.00	A		•	•				•	•					
PSDL24150	Convertisseur, 24V 150W	165.00	A		•	•				•	•					
PSDL24200	Convertisseur, 24V 200W	182.00	A		•	•				•	•					
<b>Drivers</b>																
89453829	Dali 1Ch, driver 1 canal, DALI, 12-48V DC 16A	127.00	A	•			•	•		•	•					
89453830	Dali 2Ch, driver 2 canaux, DALI, 12-48V DC 16A	147.00	A		•	•				•	•					
89453831	Dali 3Ch, driver 3 canaux, DALI, 12-48V DC 16A	158.00	A		•	•				•	•					
89453832	Dali 4Ch, driver 4 canaux, DALI, 12-48V DC 16A	173.00	A		•	•				•	•					

## Profils



AK5600  
AK5630

AK5600.B  
AK5630.B

AK5600.W  
AK5630.W

AK5700  
AK5730

AK5700.B  
AK5730.B

AK5700.W  
AK5730.W

## Embouts



AK5650

AK5650.B

AK5650.W

AK5750

AK5750.B

AK5750.W

AK5755

AK5755.B

AK5755.W

AK5760

AK5760.B

AK5760.W

## Accessoires



AC2400



AK4660



AK4665



AK5370

## Convertisseurs variables



PSDDL24150

PSDDL24240



AK5377



AK5378



AK5890



AC9500



AK5500  
AK5530

## Convertisseurs



PSDL24100



PSDL24150



PSDL24200



89453829



89453830



89453831



PSDL2430



PSDL2460



PSDL2460W



89453832